Creare un blocco ARTICOLI CORRELATI

1. Creamo una Vista, non ordinata in visualizzazione Block:

View name *		
Related nodes	Marnine name: related_nodes [Edit]	
Description		
Show Content	▼ of type Article ▼ tagged with	○ sorted by Unsorted ▼
Create a page		
🔽 Create a block 🛛 🔫 🗕		
Block title		
Related nodes		
Display format		
HTML list	of titles (linked)	
Items per page		
5		
🔲 Use a pager		
Save & exit Continue 8	& edit Cancel	

2. Aggiungiamo il campo **Content: Nid**, nelle impostazioni selezioniamo **Exclude from display** e lo spostiamo al primo posto nella lista FIELDS:

Modify the display(s) of your view below or add new displays.				Save Cancel	
Displays				edit viev	v name/description 🚽
Block* + Add					
▼ Block details					
Display name: Block					clone block
TITLE		BLOCK SETTINGS		Advanced	
Title: Related nodes		Block name: None		CONTEXTUAL FILTERS	add
FORMAT		Access: Permission View published of	content	RELATIONSHIPS	add
Format: HTML list Settings		HEADER	add	NO RESULTS BEHAVIOR	add
Show: Fields Settings		FOOTER	add	EXPOSED FORM	
FIELDS	add 💌	PAGER		Exposed form style: Basic Settings	
Content: Nid		Use pager: Display a specified number	of items 5 items	OTHER	
Content: Title		More link: No		Machine Name: block	
FILTER CRITERIA	add 💌			Comment: No comment	
Content: Published (Yes)				Use AJAX: No	
Content: Type (= Article)				Hide attachments in summary: No	
SORT CRITERIA	add			Use aggregation: No	
				Query settings: Settings	
				Field Language: Current user's language	e
				Caching: None	
				Link display: None	
				CSS class: None	
				Theme: Information	
				Block caching: Do not cache	

3. Aggiungiamo Filtro contestuale per campo del vocabolario che ci interessa (nell'esempio è field_tags):

Add contextual filters		
For All displays 📩		
Search field_tags	Filter - All -	-
Content: Tags (field_tags) Appears in: node:article.		
Content: Tags (field_tags:delta)		

4. Nelle impostazioni del filtro selezioniamo Provide default value, selezioniamo Taxonomy term ID from URL, poi Load default filter from node page, that's good for related taxonomy blocks e Filter to items that share any term. Nella sezione More marchiamo Allow multiple values

Configure contextual filter: Content: Tags (field_tags)	⊗
For All displays	
Appears in: node:article.	<u>^</u>
This display does not have a source for contextual filters, so no contextual filter value will be available unless you select 'Pro- default'.	vide
UR WHEN THE FILTER VALUE IS NOT AVAILABLE	
Display all results for the specified field	Etview
Provide default value	
Туре	
Taxonomy term ID from URL 🗾 🚤	
Load default filter from term page	
🔽 Load default filter from node page, that's good for related taxonomy blocks	
Limit terms by vocabulary	
Vocabularies	
Tags	
Multiple-value handling	
ting O Filter to items that share all terms	
Filter to items that share any term	
Hide view	
Display a summary	

Specify validation criteria	
▼ MORE Administrative title	
This title will be displayed on the views edit page instead of the default one. This might be useful if you have the same item twice. Allow multiple values If selected, users can enter multiple values in the form of 1+2+3 (for OR) or 1,2,3 (for AND).	Е
Exclude If selected, the numbers entered for the filter will be excluded rather than limiting the view.	– gs
Apply (all displays) Cancel Remove	
add 👻 Comment: No comment	

5. Aggiungiamo Filtro contestuale per **Content: Nid**, nelle impostazioni selezioniamo **Provide default value** e per **Content ID from URL**, nella sezione More spuntiamo **Exclude**

Configure contextual filter: Content: Nid			
For All displays			
The node ID.			
This display does not have a source for contextual filters, so no contextual filter value will be available unless you select 'Provide default'.			
WHEN THE FILTER VALUE IS NOT AVAILABLE			
O Display all results for the specified field			
Provide default value			
Туре			
Content ID from URL			
◎ Hide view			
Display a summary			
Display contents of "No results found"			
Skin default argument for view LIPI			
Select whether to include this default argument when constructing the URL for this view. Skipping default arguments is useful e.g. in the case of feeds.			
WHEN THE FILTER VALUE IS AVAILABLE OR A DEFAULT IS PROVIDED			
Override title			
Override breadcrumb			
Specify validation criteria			
MORE Administrative title			
This title will be displayed on the views edit page instead of the default one. This might be useful if you have the same item twice.			
Allow multiple values			
If selected, users can enter multiple values in the form of 1+2+3 (for OR) or 1,2,3 (for AND).			
🕼 Exclude			
If selected, the numbers entered for the filter will be excluded rather than limiting the view.			
(Apply (all displays) Cancel Remove			

Attenzione! Passaggi **6** e **7** servono per dare un certo ordinamento agli articoli in vista (per primo sarà visualizzato l'ultimo inserito). Nel mio caso avevo esigenza di visualizzare articoli a caso e sono passata direttamente al **Sort Criteria** e scelto la opzione **Global: Random** dopodiché ho eseguito il punto **8**.

6. Attiviamo aggregazione scegliendo "yes":

rectory.	100110	PAGE	NO RESULTS BEHAVIOR	101
Centerit; Nid		We paper. Display a specified number of news 1-3 dams	EXPOSED FORM	
Contents Title		More link: No	Exposed form dyle. Besic (Settings	
HETER ORTERIA	(and +		OTHER	
Content: Published (Yel)			Machine Name: Black	
Content: Type (+ Anticle)			Comment file comment	
SORT CRITERIA	(100)		Use ADOL: Na:	
			Hide attactionents in summary: No	
			Use apprepriation 144	_
			Query anthings: Settings	
			Field Language: Clarrent start's language	
Block: Allow group	ing and aggre	gation (calculation) of fields.		
Block: Allow group For All displays	ing and aggre	gation (calculation) of fields.		
Block: Allow group For All displays	ing and aggre	gation (calculation) of fields. available. All fields that are selected for groupin r aggregation will have the function run on the o get a list of duplicate titles.	g will be collapsed to one record p m. For example, you can group no	per distinct odes on title
Block: Allow group For All displays Aggregate If enabled, some field value. Other fields wh and count the number Apply (all display	Is may become unities a selected for er of nids in order to respect to respec	gation (calculation) of fields. available. All fields that are selected for groupin r aggregation will have the function run on the o get a list of duplicate titles.	g will be collapsed to one record p m. For example, you can group no	per distinct odes on title

7. Aggiungiamo l'ordinamento **Sort Criteria** per **Content: Nid** e come tipo di aggregazione **Aggregation type** selezioniamo **Count**

Configure group settings for sort criterion Content: Nid	
Aggregation type Count	
Select the aggregation function to use on this field.	Configure sort criterion: COUNT(Content: Nid) For All displays
Apply and continue Cancel	The node ID.
Block name: None	Expose this sort to visitors, to allow them to change it
	Sort ascending
E metodo di ordinamento cambiamo in des	Sort descending
	n s MORE

Apply (all displays)

Cancel

Remove

8. Nella pagina di amministrazione dei blocchi posizioniamo il nuovo blocco nella regione desiderata.